

TEFLEX GR-11

PTFE Graphite Packing



SPECIFICATION SHEET

Suitable For: steam, water, petroleum oils & fuels, solvents, chemicals

Operating Parameters:

Min. Temp. -200°C

Max. Temp. 260°C

Pressure:

RECIPROCATING PUMP : 100 bar (1450 psi)

ROTATING PUMP : 30 bar (430 psi)

VALVE : 200 bar (2900 psi)

Speed: 0 - 20 m/s

pH Range: 0 - 14

Colour: Black

Material: PTFE Graphite Yarn in a Lattice Braid

Available:

In an 8 metre roll or by the metre

Sizes:

3mm, 5mm, 6.4mm, 8mm, 9.5mm, 12.5mm

Physical Properties

Temperature	-200 to 260	°C
Speed	0 - 20	M/S
Density	1.35 – 1.5	g/cm³

Teflex GR-11 is a braided Graphite PTFE packing with good chemical resistance and low friction properties. It also has self-lubricating properties.

Excellent for use in Chemical plants, Gas plants, Pharmaceutical plants, power stations, Marine services, Wastewater Treatment facilities.

1404 ARTHUR PORTER DRIVE, BURBUSH, HAMILTON, NZ

PHONE: 0800 238837

EMAIL: SALES@BETTERINDUSTRIAL.CO.NZ WEB: WWW.BETTERINDUSTRIAL.CO.NZ